



SPECIFICATIONS

Current Rating: 4A AC,DC
 Voltage Rating: 125V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max.
 Insulation Resistance: 1000MΩ Min.
 Withstanding Voltage: 1000V AC/minute
 Pin Material: Brass/Tin-plated 100~150u”
 Material: Nylon 66,UL94V-0
 Color: Natural(White)

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
A2013WV-02P	2.00	5.96
A2013WV-03P	4.00	7.96
A2013WV-04P	6.00	9.96
A2013WV-05P	8.00	11.96
A2013WV-06P	10.00	13.96
A2013WV-07P	12.00	15.96
A2013WV-08P	14.00	17.96
A2013WV-09P	16.00	19.96
A2013WV-10P	18.00	21.96
A2013WV-11P	20.00	23.96
A2013WV-12P	22.00	25.96
A2013WV-13P	24.00	27.96
A2013WV-14P	26.00	29.96
A2013WV-15P	28.00	31.96

			UNIT	SCALE	SHEET	TITLE:
			mm		1 of 1	
			DRAWN BY	APPROVED BY		2.00mm PITCH 180° WAFER
			董正一	董正一		
B3	ECN NO. EN0911040539	2009.11.04	2001.02.01	2001.02.01		
B2	REVISE	2007.10.16	GENERAL TOLERANCE			
B1	REVISE	2006.05.24	X. X±0.25	ANGLE±		
B0	NEW RELEASE	2006.01.07	X. XX±0.15			
REV.	DESCRIPTION	DATE	X. XXX±0.05			DRAW NO. :
					A2013WV-XP	B3